

E - Series Water Softeners



Reduces

- ◆ Hard water deposits - calcium, magnesium plus some iron
- ◆ Scale build up on heating elements, water heaters and appliances
- ◆ Soap use and bath tube ring cleaning time



Increases

- ◆ The action of detergents, cleaners, soaps and laundry performance
- ◆ Appliance efficiency & plumbing life expectancy
- ◆ Flow rate as older plumbing is cleaned by the soft water

“Water refined one drop at a time”

MODEL	56DF2102	56DF2103	56DF2104	56DF2105
SPECIFICATIONS				
MODEL SIZE	20,000 GR	30,000 GR	40,000 GR	60,000 GR
MEDIA TANK	9"X35"	10"X35"	10"X47"	12"X52"
BRINE TANK	18"X33"	18"X33"	18"X33"	18"X40"
SALT STORAGE	326 LB	326 LB	326 LB	425 LB
RESIN VOLUME	.75 cuft	1.0 cuft	1.25 cuft	2.0 cuft
DEFAULT CAPACITY	20,000 GR	27,000 GR	34,000 GR	55,000 GR
lb's per cuft setting	10	10	10	10
SERVICE FLOW RATE@15 # psi	8	10	12	15
BACKWASH RATE (GPM)	2	2.4	2.4	4
TOTAL IRON REMOVAL (ppm)	1.5	1.5	1.5	1.5
BYPASS VALVE	INCL	INCL	INCL	INCL
CONNECTION YOKE SIZE	3/4"	3/4"	3/4"	1"
VALVE MODEL	5600 SXT	5600 SXT	5600 SXT	5600 SXT
POWER (115 VOLT AC input)	24V AC	24V AC	24V AC	24V AC
WORKING psi	20 to 125	20 to 125	20 to 125	20 to 125
INSTALLATION SPACE	18"X29"X50"	18"X30"X50"	18"X30"X62"	18"X32"X67"
SHIPPING WEIGHT (lbs)	90	105	140	155



Manufactured in Barrie Ontario with quality parts designed and sourced in North America

Features

- SXT (LED) Automatic meter initiated Fleck 5600 control
- Traditional down-flow regeneration
- The control maintains time during power interruptions up to 48 hours & cycle program is saved indefinitely
- Matching black brine tank with plastic salt grid standard (an option on many other brands)
- Vacation override feature for long periods of time with little water usage
- 5 year warranty on controls and 10 years on tank components