

# Automatic Backwashing Filters



**Professional  
Contractor's  
Products**



## Ultra Filters - Reduce

- ◆ Suspended particles, Rust, Turbidity and silt etc.  
(Often pre treatment to R/O drinking water systems)
- ◆ Cartridge filter waste and time changing POU filter elements

## Carbon Filters - Reduce

- ◆ Taste and Odour, such as harsh chlorine residual
- ◆ Warm lake water musty odours
- ◆ Organic colour and tannins staining

## Neutralizers - Reduce

- ◆ Low pH conditions where plumbing fixtures and appliances can often be damaged  
(many surface waters and some wells are low pH as they are effected by "acid rain")
- ◆ Corrosion when copper and other piping is being attacked, giving off blue/green water stains.



Manufactured in Barrie Ontario with quality parts designed and sourced in North America  
**5 year warranty on controls and 10 years on tank components**

MODEL	ULTRA FILTER	ULTRA FILTER	ULTRA FILTER	CARBON FILTER	CARBON FILTER	CARBON FILTER	NEUTRALIZER	NEUTRALIZER	NEUTRALIZER
	58LX4909	58LX4910	58LX4911	58LX4629	58LX4630	58LX4631	58LX4641	58LX4642	58LX4643
<b>SPECIFICATION</b>									
MODEL SIZE	ULTRAMF 1.0 LXT	ULTRAMF 1.5 LXT	ULTRAMF 2.0 LXT	ACF 1.0 LXT	ACF 1.5 LXT	ACF 2.0 LXT	NF 1.0 LXT	NF 1.5 LXT	NF 2.0 LXT
MEDIA TANK	9"X48"	10"X54"	12"X52"	9"X48"	10"X54"	12"X52"	9"X48"	10"X54"	12"X52"
RESIN VOLUME	1.0 cuft	1.5 cuft	2.0 cuft	1.0 cuft	1.5 cuft	2.0 cuft	1.0 cuft	1.5 cuft	2.0 cuft
SERVICE FLOW RATE (GPM)	5 - 8.5	7 - 11.0	10 - 15.5	5 - 7.0	6 - 10.0	9 - 12.0	3 - 5.0	4 - 8.0	6 - 10.0
BACKWASH RATE (GPM)	5	10	12	5	6	7	4	7	8
BYPASS VALVE	INCL	INCL	INCL	INCL	INCL	INCL	INCL	INCL	INCL
CONNECTION YOKE SIZE	3/4"	3/4"	1"	3/4"	3/4"	1"	3/4"	3/4"	1"
VALVE MODEL	5800 LXT	5800 LXT	5800 LXT	5800 LXT	5800 LXT	5800 LXT	5800 LXT	5800 LXT	5800 LXT
POWER (115 VOLT AC input)	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC
WORKING (psi)	20 to 125	20 to 125	20 to 125	20 to 125	20 to 125	20 to 125	20 to 125	20 to 125	20 to 125
INSTALLATION SPACE	11"X11"X63"	12"X12"X69"	14"X14"X67"	11"X11"X63"	12"X12"X69"	14"X14"X67"	11"X11"X63"	12"X12"X69"	14"X14"X67"
SHIPPING WEIGHT (lbs)	145	213	265	65	95	105	115	165	215
LOADED MEDIA	YES	YES	NO	YES	YES	YES	YES	YES	NO



Control Tested and Certified by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.

Control Tested and Certified by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.