

# Hi Flo - Water Softeners



## Reduces

- ◆ Hard water deposits - calcium, magnesium plus some iron
- ◆ Scale build up on heating elements, water heaters and appliances
- ◆ Soap use and bath tube ring cleaning time



## Increases

- ◆ The action of detergents, cleaners, soaps and laundry performance
- ◆ Appliance efficiency & plumbing life expectancy
- ◆ Flow rate as older plumbing is cleaned by the soft water

*“Water refined one drop at a time”*

MODEL	58104200	58104201	58104202
<b>SPECIFICATIONS</b>			
MODEL SIZE	30,000 GR	40,000 GR	60,000 GR
MEDIA TANK	10"X35"	10"X47"	12"X52"
BRINE TANK	18"X33"	18"X33"	18"X40"
SALT STORAGE	326 LB	326 LB	425 LB
RESIN VOLUME	1.0 cuft	1.25 cuft	2.0 cuft
DEFAULT CAPACITY	23,000 GR	28,700 GR	46,000 GR
lb's per cuft setting	6	6	6
SERVICE FLOW RATE@15 # psi	10	12	15
BACKWASH RATE (GPM)	2.4	2.4	4
TOTAL IRON REMOVAL (ppm)	1.5	1.5	1.5
BYPASS VALVE	INCL	INCL	INCL
CONNECTION YOKE SIZE	1"	1"	1"
VALVE MODEL	5810 SXT	5810 SXT	5810 SXT
POWER (115 VOLT AC input)	12V DC	12V DC	12V DC
WORKING psi	20 to 125	20 to 125	20 to 125
INSTALLATION SPACE	18"X30"X50"	18"X30"X62"	18"X32"X67"
SHIPPING WEIGHT (lbs)	105	140	155



Manufactured in Barrie Ontario with quality parts designed and sourced in North America

## Features

- **SXT (LED) Automatic meter initiated Fleck 5810 - 1" control**
- **The latest Pentair valve design features with photo sensor, cycle technology**
- **The control maintains time during power interruptions up to 48 hours & cycle program is saved indefinitely**
- **Matching black brine tank with plastic salt grid standard (an option on many other brands)**
- **Vacation override feature for long periods of time with little water usage**
- **5 year warranty on controls and 10 years on tank components**



Control Tested and Certified by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.

Control Tested and Certified by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.