

# Premium Water Softeners



## Reduces

- ◆ Hard water deposits - calcium, magnesium plus iron
- ◆ Scale build up on heating elements
- ◆ Soap use and bath tube ring scum

## Increases

- ◆ The action of soap, detergents and cleaners
- ◆ Plumbing performance and reduces flow issues
- ◆ Appliance efficiency and life expectation



*“Water refined one drop at a time”*

MODEL	58UF4623	58UF4624	58UF4625	58UF4626
<b>SPECIFICATIONS</b>				
MODEL SIZE	20,000 GR	30,000 GR	40,000 GR	60,000 GR
MEDIA TANK	9"X35"	10"X35"	10"X47"	12"X52"
BRINE TANK	18"X33"	18"X33"	18"X33"	18"X40"
SALT STORAGE	326 LB	326 LB	326 LB	425 LB
RESIN VOLUME	.75 cuft	1.0 cuft	1.25 cuft	2.0 cuft
DEFAULT CAPACITY	16,200 GR	23,000 GR	28,700 GR	46,000 GR
lb's per cuft setting	6	6	6	6
SERVICE FLOW RATE@15 #pd	8	10	12	15
BACKWASH RATE (GPM)	2	2.4	2.4	4
TOTAL IRON REMOVAL (ppm)	1.5	1.5	1.5	1.5
BYPASS VALVE	INCL	INCL	INCL	INCL
CONNECTION YOKE SIZE	3/4"	3/4"	3/4"	1"
VALVE MODEL	5800 SXT	5800 SXT	5800 SXT	5800 SXT
POWER (115 VOLT AC input)	12V DC	12V DC	12V DC	12V DC
WORKING psi	20 to 125	20 to 125	20 to 125	20 to 125
INSTALLATION SPACE	18"X29"X50"	18"X30"X50"	18"X30"X62"	18"X32"X67"
SHIPPING WEIGHT (lbs)	90	105	140	155



Manufactured in Barrie Ontario with quality parts designed and sourced in North America

## Features

- **SXT (LED) Automatic meter initiated regeneration with the latest technology (Fleck 5800SXT control)**
- **These models save water and salt over many other brands**
- **Upflow regeneration provides maximum efficiency and resin cleaning during each cycle**
- **The control maintains time during power interruptions up to 48 hours & cycle program is saved indefinitely**
- **Soft water brine refill keeps the brine tank clean**
- **5 year warranty on control and 10 year on tank components**



Control Tested and Certified by the WQA to NSF/ANSI Standard 44 for Water Softener Performance.

Control Tested and Certified by the WQA to NSF/ANSI Standard 372 for Lead Free Compliance.